



rangehood solutions

Whatever your need, Omega has a rangehood solution for you, from undermount and hidden in your cabinetry, to telescopic, to full chimney designs, in widths from 60cm to 90cm.

In a wall mount or island setting, an Omega rangehood is not only powerful and highly functional, but can also be a visual enhancement to any kitchen.

You also have the option to choose to have your Omega rangehood ducted direct to atmosphere or filtered recirculated, or have a remote motor installed to reduce sound.

glass

4 SPEED	WALL MOUNT		OR907CXA		WIDTH	
			760 m ³ /hr NETT	988 m ³ /hr GROSS		
			<p>stainless steel and glass 900mmW x 480mmD x max 1005mmH duct direct to atmosphere or recirculate to kitchen 150mm diameter ducting required twin halogen lights 4 speeds, separate buttons delay stop timer selection 34-56 dBA noise rating grease filter: removable and washable single 4 ply aluminium</p>		CODE OR907CXA	90 cm

			FM909		3 SPEED
WIDTH		760 m ³ /hr NETT	988 m ³ /hr GROSS		
CODE FM909	<p>polished stainless steel and clear tempered glass 900mmW x 480mmD x 910mmH duct direct to atmosphere or recirculate to kitchen 150mm diameter ducting required twin 20 watt halogen lights, separate button 3 speeds, separate buttons delay stop timer selection 36-59 dBA noise rating grease filter: removable and washable single 5-ply aluminium</p>				WALL MOUNT
90 cm					

		K224/1X90		
3 SPEED		760 m ³ /hr NETT	942 m ³ /hr GROSS	WIDTH
WALL MOUNT		<p>all stainless steel 900mmW x 480mmD x max 1340mmH duct direct to atmosphere or recirculate to kitchen twin halogen lights, separate button, 3 speeds plus off, separate buttons 44-60 dBA noise rating 150mm diameter ducting required grease filters: removable and washable 3 x 4-ply aluminium activated charcoal filter pair part number 31264001</p>		CODE 13405
				90 cm



		OR701CXA		
WIDTH		510 m ³ /hr NETT	663 m ³ /hr GROSS	3 SPEED
CODE OR701CXA		<p>all stainless steel 700mmW x 480mmD x max 1140mmH duct direct to atmosphere or recirculate to kitchen 150mm ducting required 2 x 40 watt incandescent lights, separate button, three speeds plus off, separate buttons 41-53 dBA noise rating grease filters: removable and washable 2 x 4-ply aluminium activated charcoal filter pair part number 08999801</p>		WALL MOUNT
	70 cm			



		K224/1X60		
3 SPEED		760 m ³ /hr NETT	942 m ³ /hr GROSS	WIDTH
WALL MOUNT		<p>all stainless steel 600mmW x 480mmD x max 1340mmH duct direct to atmosphere or recirculate to kitchen twin halogen lights, separate button, 3 speeds plus off, separate buttons 44-60 dBA noise rating 150mm diameter ducting required grease filters: removable and washable 2 x 4-ply aluminium activated charcoal filter pair part number 31264001</p>		CODE 13411
				60 cm





WALL PLATES

all stainless steel wallplates in two widths to suit 60cm or 90cm cooktops and rangehoods

Shown at left with 900mm x 1600mm wall plate: K224/1X90 90cm stainless steel rangehood above OF901XA 90cm stainless steel freestanding cooker

CODE 2958

90
x160

900mm x 1600mm

CODE 14202

90
x65

900mm x 650mm

CODE 14201

60
x65

600mm x 650mm



		OR912CXA			
3 SPEED		700 m ³ /hr NETT	910 m ³ /hr GROSS		WIDTH
WALL MOUNT		stainless steel and black glass facia 900mmW x 500mmD x max 1050mmH duct direct to atmosphere or recirculate to kitchen twin halogen lights, separate touch pad, 3 speeds plus off, separate touch pad 5 minute delay stop selection 36-59 dBA noise rating 150mm diameter ducting required grease filters: removable and washable 3 x 5-ply aluminium			CODE OR912CXA
					90 cm



		OR911CXA			
3 SPEED		700 m ³ /hr NETT	910 m ³ /hr GROSS		WIDTH
WALL MOUNT		all stainless steel 900mmW x 500mmD x max 1050mmH duct direct to atmosphere or recirculate to kitchen twin halogen lights, separate button 3 speeds plus off, separate buttons 5 minute delay stop selection 36-59 dBA noise rating 150mm diameter ducting required grease filters: removable and washable 3 x 5-ply aluminium			CODE OR911CXA
					90 cm



		K7052			
WIDTH		460 m ³ /hr NETT	598 m ³ /hr GROSS		3 SPEED
CODE 3152/90		all stainless steel 900mmW x 500mmD x max 1240mmH duct direct to atmosphere or recirculate to kitchen twin 40 watt incandescent lights, separate button 3 speeds, separate buttons 38-53 dBA noise rating grease filters: removable and washable 3 x 4-ply aluminium charcoal filter part number 08999802			WALL MOUNT
90 cm					

remote motor

4 SPEED		POR905CRXA		WIDTH
		REMOTE SILENT PACK		
WALL MOUNT		950 m ³ /hr NETT	1,235 m ³ /hr GROSS	CODE ORP905CRXA
		<p>all stainless steel 900mmW x 500mmD x max 1010mmH must be ducted to remotely installed EMD950 motor 150mm diameter ducting required. twin halogen lights, separate touch pad 4 speeds, separate touch pad 5 minute delay stop selection 30 hour grease filter cleaning prompt LED indicator noise rating: not applicable - no motor is installed in the actual rangehood unit grease filters: 3 x removable and washable 4-ply stainless steel/aluminium</p>		
		<p>EMD950 REMOTE MOTOR 445mm x 430mm x 280mm all stainless steel inlet outlet 150mm diameter noise rating 68dBA</p>		90 cm
				

island

3 SPEED		IS20X		WIDTH
		ISLAND MOUNT		
ISLAND MOUNT		720 m ³ /hr NETT	936 m ³ /hr GROSS	CODE IS20X90
		<p>all stainless steel 900mmW x 600mmD x max 1155mmH duct direct to atmosphere or recirculate to kitchen 4 x halogen lights, separate button 3 speeds, separate buttons grease filters: removable and washable 6 x 4-ply stainless steel/aluminium activated charcoal filter pair part number 03300416</p>		
				90 cm

K296X

3
SPEED

BUILT IN OR FREESTANDING

450
m³/hr
NETT

585
m³/hr
GROSS

WIDTH

WIDTH



twin motor
600mm W [900mm] x 500mmD x 140mmH
all stainless steel with fixed glass visor
rear or top direct duct to atmosphere, 125mm diameter
ducting required
front recirculate to kitchen
twin 40 watt incandescent lights, separate button
3 speeds, separate buttons
removable and washable 4-ply aluminium grease filter[s]
60cm charcoal filter 08999713 or cartridge pair 03300416
90cm charcoal filter 08999714 or cartridge pair 03300416

CODE 2292

CODE 2296/2

60
cm

90
cm

OA2001X

3
SPEED

BUILT IN OR FREESTANDING

260
m³/hr
NETT

338
m³/hr
GROSS

WIDTH

WIDTH



single motor
600mmW [900] x 482mmD x 140mmH
rear or top direct duct to atmosphere
125mm diameter ducting required
front recirculate to kitchen
40 watt incandescent light, separate slide switch position
3 speeds, separate slide switch positions
removable and replaceable cloth filter
60 and 90cm charcoal filter part number 03300437

CODE 2003/1

CODE 2008/1

60
cm

90
cm

OA2001W60

60cm model available in white
CODE 2001

OA2001W90

90cm model available in white
CODE 2006/1

ORF6X

ORF9X

WIDTH

WIDTH

210
m³/hr
NETT

270
m³/hr
GROSS

BUILT IN OR FREESTANDING

3
SPEED

CODE ORF6X

CODE ORF9X

single motor
600mmW [900] x 500mmD x 140mmH
freestanding or built in, fixed glass visor
rear or top direct duct to atmosphere
120mm diameter ducting required
front recirculate to kitchen
3 speeds, separate buttons plus off button
2 x 40 watt incandescent lights, separate button
grease filters:
removable and washable 2 [3] x 4-ply aluminium



60
cm

90
cm

ORF6W

60cm model available in white
CODE ORF6W

ORF9W

90cm model available in white
CODE ORF9W

concealed

		OR521UXA	
		OR701UXA	
WIDTH	WIDTH	750 m ³ /hr NETT	975 m ³ /hr GROSS
CODE OR701UXA	CODE OR521UXA	centrifugal motor twin impellers 520mmW [700] x 285mmD x 315mmH concealed, all stainless steel LED indicator for speed, delay stop and prompts twin halogen lights, separate button. 4 speeds, separate button 5 minute delay stop, separate button 30 hour grease filter cleaning prompt 120 hr charcoal filter inspection prompt, reset button 150mm or 125mm diameter ducting required 150/125mm diameter adaptor supplied duct direct to atmosphere or recirculate to kitchen optional charcoal filter pair part number 08999801	
70 cm	52 cm		



4
SPEED

UNDERMOUNT

		P194	
WIDTH	WIDTH	380 m ³ /hr NETT	494 m ³ /hr GROSS
CODE 3004	CODE 3003	twin motor 520mmW [700] x 280mmD x 182mmH concealed, silver frost incandescent 40 watt globes, slide switch 3 speeds, slide switch 125 mm diameter ducting required for direct ducting to atmosphere or recirculating to kitchen charcoal filter pair part number 03300416	
70 cm	52 cm		



3
SPEED

UNDERMOUNT

OA412FR60X

OA412FR90X

WIDTH	WIDTH		260 m ³ /hr NETT	338 m ³ /hr GROSS
CODE 3081/3	CODE 3077/3	single motor, stainless steel facia rail, glass deflector twin 40 watt S.E.S tubular globes separate pre-settable switch 3 x speed pre-settable switch removable filter carriage (1 x 60cm, 2 x 90cm) removable washable 4 ply aluminium grease filter designed for recirculation, return vent concealed behind 80mm high retractable facia rail - no ducting required NB. can be ducted direct to atmosphere, 125mm dia. ducting required 37-53 dBA noise rating replaceable charcoal filter supplied 08999875 (60cm), 08999824 (90cm)		
90 cm	60 cm			



3
SPEED

SINGLE MOTOR

OR603TWA

OR903TWA

WIDTH	WIDTH		260 m ³ /hr NETT	338 m ³ /hr GROSS
CODE OR903TWA	CODE OR603TWA	single motor, enamelled white facia rail, glass deflector twin 40 watt S.E.S tubular globes separate pre-settable switch 3 x speed pre-settable switch removable washable 4 ply aluminium grease filter designed for recirculation, return vent concealed behind 80mm high retractable facia rail - no ducting required NB. can be ducted direct to atmosphere, 125mm dia. ducting required 37-53 dBA noise rating replaceable charcoal filter supplied 08999875 (60cm), 08999824 (90cm)		
90 cm	60 cm			



3
SPEED

SINGLE MOTOR

OR601TWA

WIDTH		260 m ³ /hr NETT	338 m ³ /hr GROSS
CODE OR601TWA	single motor, enamelled white facia rail and deflector twin 40 watt S.E.S tubular globes separate pre-settable switch 3 x speed pre-settable switch removable washable 3 ply aluminium grease filter designed for recirculation, return vent concealed behind 80mm high retractable facia rail - no ducting required NB. can be ducted direct to atmosphere, 125mm dia. ducting required 37-53 dBA noise rating optional replaceable charcoal filter 08999875		
60 cm			



3
SPEED

SINGLE MOTOR

telescopic

OA2416X60

OA2416X90

WIDTH	WIDTH		390 m ³ /hr NETT	507 m ³ /hr GROSS
CODE 3128/3	CODE 3137/3	twin motor, stainless steel facia rail, white enamel deflector twin 40 watt S.E.S tubular globes separate pre-settable switch 3 x speed pre-settable switch removable filter carriage (1 x 60cm, 2 x 90cm) removable washable 4 ply aluminium grease filters duct direct to atmosphere or recirculate 125mm dia. ducting required 39-64 dBA noise rating optional charcoal filter - 08999875 (60cm), 08999824 (90cm)		
90 cm	60 cm			



3
SPEED

TWIN MOTOR

OA416W/X60

OA416W/X90

WIDTH	WIDTH		260 m ³ /hr NETT	338 m ³ /hr GROSS
CODE 3033/3	CODE 3031/3	single motor, stainless steel facia rail, white enamel deflector twin 40 watt S.E.S tubular globes separate pre-settable switch 3 x speed pre-settable switch removable filter carriage (1 x 60cm, 2 x 90cm) removable washable 4 ply aluminium grease filter duct direct to atmosphere or recirculate 125mm dia. ducting required 37-53 dBA noise rating optional charcoal filter - 08999875 (60cm), 08999824 (90cm)		
90 cm	60 cm			



3
SPEED

SINGLE MOTOR

OR605TXA

OR905TXA

WIDTH	WIDTH		300 m ³ /hr NETT	390 m ³ /hr GROSS
CODE OR905TXA	CODE OR605TXA	single motor, retractable glass visor twin 40 watt incandescent lights, separate on/off button 3 speeds, separate buttons direct ducting to atmosphere or re-circulate to kitchen 125mm diameter ducting required 43-54 dBA noise rating optional charcoal filter 03300437		
90 cm	60 cm			



3
SPEED

SINGLE MOTOR